


	Tłumienie dźwięku w tłumikach A125 - A400 dL, dB, wg. PN-EN ISO 7235					
	Średnica D, mm, długość L 600 mm					
Częstotliwość f, Hz	125	160	200	250	315	400
	Tłumienie dźwięku dL, dB					
63	2	1	1	0	0	0
125	2	1	1	1	1	0
250	3	3	3	3	3	4
500	4	4	4	4	4	6
1000	12	12	12	11	11	10
2000	9	11	13	14	16	17
4000	8	9	10	12	15	20
8000	8	8	10	12	14	16

	<i>Tłumienie dźwięku w tłumikach A125 - A400 dL, dB, wg. PN-EN ISO 7235</i>					
	<i>Średnica D, mm, długość L 1000 mm</i>					
<i>Częstotliwość f, Hz</i>	125	160	200	250	315	400
	<i>Tłumienie dźwięku dL, dB</i>					
63	3	2	1	0	0	0
125	3	2	2	2	1	0
250	5	5	5	5	5	7
500	7	7	6	6	7	10
1000	20	20	19	18	18	16
2000	16	19	21	24	27	28
4000	14	15	17	19	24	33
8000	14	15	17	19	23	27

	Tłumienie dźwięku w tłumikach A125 - A400 dL, dB, wg. PN-EN ISO 7235					
	Średnica D, mm, długość L 1200 mm					
Częstotliwość f, Hz	125	160	200	250	315	400
	Tłumienie dźwięku dL, dB					
63	3	2	1	0	0	0
125	3	3	3	2	1	0
250	6	6	6	6	7	9
500	8	8	8	8	9	12
1000	24	24	23	22	21	19
2000	19	22	26	29	32	33
4000	17	18	20	23	29	39
8000	16	18	20	23	27	32

	<i>Spadek ciśnienia dP, Pa dla tłumików A /125 - A /400 wg. PN EN ISO 5801</i>					
	Średnica D , mm					
Wydatek Q , m^3/h	125	160	200	250	315	400
	Spadek ciśnienia dP , Pa					
50	0	0	0	0	0	0
100	2	1	0	0	0	0
150	6	2	1	1	0	0
200	11	4	2	1	0	0
250	18	6	3	2	1	0
300	28	9	4	3	1	0
400	54	16	7	5	1	1
500	91	25	11	7	2	1
600	139	37	16	9	2	1
700	199	51	22	12	3	2
800		68	28	16	4	2
900		87	36	19	5	3
1000		109	44	23	6	4
1500		258	99	47	12	7
2000			176	77	21	12
2500			276	114	31	18
3000				157	43	25
3500				205	56	33
4000					71	41
4500					88	51
5000					106	61
5500					126	72
6000					147	84
6500					169	97
7000					193	111
7500						125
8000						141

TŁUMIKI WENTYLACYJNE